



info@fach-pak.com www.fach-pak.com

Type 460

Dimensions: 1230 x 1030 x 580 mm


Capacity: 445 L Skin material: MDPE


Insulation core: expanded PE or closed cell PU


Wall thickness: 30 mm


Weight: 51 kgs (EPE) / 42 kgs (PU)
Drain holes: 0 - 1 - 2 - 3 - 4 / 2" BCS 56 x 4

Option: drain hole 2" BSP Stackable with: type 650, 660









720





info@fach-pak.com www.fach-pak.com

Type 630


Dimensions: 1200 x 1000 x 785 mm


Capacity: 630 L
Skin material: MDPE
Insulation core: expanded PE
Wall thickness: 32,5 mm
Weight: 65 kgs

Drain holes: 0 - 1 - 2 / 2" BCS 56 x 4


Options: bottom protrusion, drain hole 2" BSP


handle recessess on corners











Dimensional tolerance \pm 3%, any changes and errors reserved.

All technical data provided are guide values. They may vary because of specific applications and conditions The information provided are based on the current knowledge and experience. The user is obliged to carry out its own tests and inspections before regular usage of the product.





info@fach-pak.com www.fach-pak.com

Type 660 - short forklift passage

Dimensions: 1230 x 1030 x 750 mm


Capacity: 620 L Skin material: MDPE


Insulation core: expanded PE or closed cell PU

Wall thickness: 30 mm


Weight: 62 kgs (EPE) / 52 kgs (PU)
Drain holes: 0 - 1 - 2 - 3 - 4 / 2" BCS 56 x 4


Option: drain hole 2" BSP Stackable with: type 650, 660











Dimensional tolerance ± 3%, any changes and errors reserved.
All technical data provided are guide values. They may vary because of specific applications and conditions The information provided are based on the current knowledge and experience. The user is obliged to carry out its own tests and inspections before regular usage of the product.





info@fach-pak.com www.fach-pak.com

Type 660 - wide forklift passage

Dimensions: 1230 x 1030 x 750 mm

Capacity: 620 L Skin material: MDPE


Insulation core: expanded PE or closed cell PU

Wall thickness: 30 mm


Weight: 63 kgs (EPE) / 52 kgs (PU)
Drain holes: 0 - 1 - 2 - 3 - 4 / 2" BCS 56 x 4


Options: bottom protrusions, drain hole 2" BSP


Stackable with: type 650, 660











Dimensional tolerance ± 3%, any changes and errors reserved.
All technical data provided are guide values. They may vary because of specific applications and conditions The information provided are based on the current knowledge and experience. The user is obliged to carry out its own tests and inspections before regular usage of the product.